
LWBD-175 Series






Product Characteristic


- Impeller Material: Plastic PA66+25GF
- Motor Type: BLDC
- Direction of Rotation: Clockwise,seen on rotor
- Mode of Operation: S1
- Protection Class: IP42
- Insulation Class: F
- Mounting Position: Horizontal or Vertical
- Operation Temperature: -25℃～+60℃
- Bearing: Maintenance-free ball bearings
- Technical Features: Control input 0-10VDC/PWM
- Protection: Tach output,Locked-Rotor protection Reverse Polarity,Over-voltage protection,Soft Start

Technical Specifications

Model	Voltage (V)	Current (A)	Rated Power (W)	Speed (RPM)	Air Volume (m^3/h)	Static Pressure (Pa)	Noise [dB(A)]
LWBD3G175-072NM-02	24	3.2	75	3900	618	515	71
LWBD3G175-072NH-03	48	1.5	75	3900	618	515	71



LWBD-175 Series





Product Characteristic

- Impeller Material: Plastic PA66+25GF
- Motor Type: BLDC
- Direction of Rotation: Clockwise,seen on rotor
- Mode of Operation: S1
- Protection Class: IP42
- Insulation Class: F
- Mounting Position: Horizontal or Vertical
- Operation Temperature: -25℃～+60℃
- Bearing: Maintenance-free ball bearings
- Technical Features: Control input 0-10VDC/PWM
- Protection: Tach output,Locked-Rotor protection Reverse Polarity,Over-voltage protection,Soft Start

Technical Specifications

Model	Voltage (V)	Current (A)	Rated Power (W)	Speed (RPM)	Air Volume (m^3/h)	Static Pressure (Pa)	Noise [dB(A)]
LWBD3G175-072NM-04	24	2.1	50	2800	670	319	68

