

1		2		3		4		5		6		7		8	
A															
B		SPECIFICATION													
		VOLTAGE (V)		220-240V											
		FREQUENCY (Hz)		50											
C		T1		CoolingCapacity (BTU/h)		24000									
				CoolingCapacity (W)		6810(1830~7800)									
				Input Power (W)		2350(410~2830)									
				RatedCurrent (A)		10.5(2.3~12.3)									
				EER		2.9									
D		T3		CoolingCapacity (BTU/h)		20400									
				CoolingCapacity (W)		5980									
				Input Power (W)		2800									
				RatedCurrent (A)		12.5									
				EER		2.14									
E		Heating		HeatingCapacity (BTU/h)		24000									
				HeatingCapacity (W)		6870(1850~7900)									
				Input Power (W)		2240(420~3000)									
				RatedCurrent (A)		10(2.3~13.5)									
				COP		3.07									
				MaximumInput Power (W)		3100									
				MaximumCurrent (A)		14.8									
				Indoor Air Volume (m³/h)		1050/950/800/680									
				Rated Input Power (W)		45									
F				DehumidificationCapacity (kg/h)		2.6									
				Noise (dB(A))		49/47/45/42									
				Body Size (W×H×D)		1075x330x240									
				Noise (dB)		59									
				Body Size (W×H×D)		850(780)x350x600									

										Stage Mark				Material			Ratio	1:2.5	Weight		
										S										Ningbo Longwell Electric Technology Co., Limited	
						Design	HE	20260327	LWHA-CH68-01A												
						Audit															
						Technical															
						Standard															
Mark	Qty		Sign	Name	Date	Approve			第 1 页		共 1 页		8								