SPECIFICATION

	VOLTAGE (V)	220-240V
	FREQUENCY (Hz)	50
T1	CoolingCapacity (BTU/h)	18000
	CoolingCapacity (W)	5100(1250~5910)
	Input Power (W)	1690(330~2340)
	RatedCurrent (A)	7.5(1.7~12)
	EER	3.02
T3	CoolingCapacity (BTU/h)	15300
	CoolingCapacity (W)	4490
	Input Power (W)	2000
	RatedCurrent (A)	8.9
	EER	2.25
Heating	HeatingCapacity (BTU/h)	18000
	HeatingCapacity (W)	5100(1250~6070)
	Input Power (W)	1620(340~2520)
	RatedCurrent (A)	7.2(1.7~13)
	COP	3.15
	MaximumInput Power (W)	2520
	MaximumCurrent (A)	13
	Indoor Air Volume (m^3/h)	850/750/650/580
	Rated Input Power (W)	35W
	DehumidificationCapacity (kg/h)	2
	Noise (dB(A))	45/42/39/37
	Body Size (W×H×D)	910x295x205
	Noise (dB)	55
	Body Size (W×H×D)	830(760)X305X550

Mark	Qty	Sign	Name	Date			
					Stage Mark		
					S		
					A1		
					Design	HE	20260327
					Audit		
					Technical		
					Standard		
					Approve		

Material		Ratio	1:2.5	Weight	

Ningbo Longwell Electric Technology Co., Limited

LWHA-CH51-01A

第 1 页 共 1 页