



Technical Request

1. The appearance and surface of the product should be clean, without rust spots, mildew, scratches, No obvious burr and other surface defects.
2. Shell riveted firmly, no obvious gap, size in line with the drawing requirements.
3. Diagonal flow, 22 blades, steel shaft  $\phi 3$ , bushing  $\phi 1.5$
4. Impeller direction: left rotation, sleeve built-in.
5. Safety performance in accordance with GB/T13933-2008 regulations.
6. Unnoted tolerance is GB/T1804-v.

No.	Item	Material	Qty
1	Motor	4820	1
2	Right Side Plate	Iron	1
3	Air Outlet Plate	Iron	1
4	Air Inlet Plate	Iron	1
5	Impeller	Al	1
6	Left Side Plate	Iron	1

公共档 黑 (Black)  
红 (Red)

SPECIFICATION

VOLTAGE (V)	AC 220V
FREQUENCY (Hz)	50
SPEED (r/min)	2050±150
AIR VOLUME (m <sup>3</sup> /h)	/
BEARINGS	Ball bearing
INPUT POWER (W)	/

					Stage Mark		Material		Ratio	1:1	Weight	
					S			Ningbo Longwell Electric Technology Co., Limited				
					Version	Name	Date	LWCA-40270SN-06-00				
					A1	GUO	20260328					
					Design							
					Audit							
					Technical							
					Standard							
Mark	Qty	Sign	Name	Date	Approve							