



1. The appearance and surface of the product should be clean, without rust spots, mildew, scratches, No obvious burr and other surface defects.
2. Shell riveted firmly, no obvious gap, size in line with the drawing requirements.
3. Make the impeller 22 blades, steel shaft $\varnothing 3$, bushing $\varnothing 1.5$
4. Safety performance in accordance with GB/T13933-2008 regulations.
5. Unnoted tolerance is GB/T1804-v.

SPECIFICATION	
VOLTAGE (VDC)	24
CURRENT (A)	0.5±10%
SPEED (r/min)	2200±10%
BEARINGS	Ball bearing
SPEED CONTROL	0-10V

7		Grille	1	Aluminium						
6		Left Side Plate	1	Iron						
5		Impeller	3	Aluminium						
4		Air Outlet Plate	1	Aluminium						
3		Air Inlet Plate	1	Aluminium						
2		Right Side Plate	1	Iron						
1	53	Motor	1							
序号	代号	名称	数量	材料	单件	总计	备注			
					重量					
		Stage Mark		Material		Ratio	1:1	Weight		
		S			Ningbo Longwell Electric Technology Co., Limited					
		Version	A1	Name	Date	LWCD-401286MN-06-16				
		Design	GU0	20260709						
		Audit								
		Technical								
		Standard								
Mark	Qty	Sign	Name	Date	Approve			第 1 页		共 1 页